

CAR PAINT
SIMPLY MIXED
TO PERFECTION

GERMANY

Optimized mixing speed due to 4 digital speed levels

More power – top results even when using heavy containers

Increased stability





Excellent mixing results

Ideal for use in auto body shops and collision repair centers

Cost and time savings

Replaces time-consuming stirring by hand

Ultimate color precision

Perfect and foam-free mixing results

Reliable color consistency

Even with metallic paints that are difficult to mix

Economical

Avoid costly reworking due to mixing problems

Greater mixing performance

Increased stability at higher speeds. Best used in combination with the ROTOGEN BASE 2.

Technical data

CAN SPECIFICATIONS	
Mixing weight	up to 2 kg (max. 1 ltr.)
Mixing capacity	50 - 1000 ml
Max. container diameter	110 mm
Type of containers	round / oval / metal / plastic
Additional containers	wide variety of adapters available
PERFORMANCE	
Power rate	230 V/50 Hz (optional 120 V/60 Hz
Power rating	60 VA
Speed	250 • 290 • 320 • 340 rpm
ANDLING	
Mixing times	freely selectable
Safety	Auto-stop function
HIPPING / INSTALLATION	
Machine dimensions (w x d x h)	360 x 420 x 300 mm
Machine weight	13.7 kg
Packaging dimensions (w x d x h)	410 x 500 x 340 mm
Packaging weight	3.6 kg





| Accessories and adapters

The Rotogen 2 is available with two different adapter containers (holding cups):

Standard holding cup in turquoise (Ref. No. 72850): for mixing quantities from **0 – 1.0 kg**

Optional holding cup in black (Ref. No. 72851): for mixing quantities from 1.0 – 2-0 kg

 Collomix offers adapters for all standard mixing paint cans and mixing cup systems for paint guns, e.g. from SATA, 3M and many more

» You can find the appropriate adapters in the "ROTOGEN 2- Accessories and adapters" sheet or scan the QR code





Your Distributors

Collomix GmbH

Daimlerstraße 9 85080 Gaimersheim GERMANY

P: +49 (0) 8458 / 32 98 0 F: +49 (0) 8458 / 32 98 30 E: info@collomix.de

www.collomix.com